

10 PIN

**CAVO ENCODER + CONNETTORE VOLANTE 10 pin (Versione OEMER)
ENCODER CABLE + 10 pin FLYING CONNECTOR (OEMER Version)**



Cavo flessibile schermato per posa mobile in PUR
Lato motore: Connettore femmina volante size 18, 10 pin
saldato secondo lo schema sotto riportato.
Lato inverter: cavi liberi spelati e terminati, pronti per il
collegamento alla morsettiera/connettore dell'inverter.

PUR Flexible shielded encoder cable for chains.
*Motor side: 10 pin size 18 female flying connector welded in
accordance with the diagram below.*
*Inverter side: free cables ready to be connected to the inverter
terminal board/connector.*


SPECIFICHE CAVO – CABLE SPECIFICATION

Cavo Encoder 3x2x0,34+2x0,5 schermato PUR +
Connettore 10 Pin
*Encoder Cable 3x2x0,34+2x0,5 shielded PUR +
10 Pin Connector*

**Lunghezze Standard Disponibili
Standard Length Available**

5mt
10mt
15mt
20mt
25mt

CONNESSIONI E COLORI CAVO – CONNECTION AND CABLE COLORS



PIN	Incremental TTL – HTL	Incremental Sinus 1Vp/p	Absolute Sincos Hiperface	Colore Cavo - Cable Color
A	A	COS+	SIN+	Bianco – White
B	Z	Z	Data+	Viola – Purple (Verde – Green)
C	B	SIN+	COS+	Rosa – Pink
D	-	-	-	-
E	SHIELD	SHIELD	SHIELD	Giallo/Marrone - Yellow/Brown (Bianco/Rosso - White/Red)
F	+Vdc	+Vdc	+Vdc	Rosso – Red
G	0V...(GND)	0V...(GND)	0V...(GND)	Blu – Blue
H	A-	REF COS (COS-)	REF SIN	Marrone – Brown
I	Z-	Z-	Data-	Giallo – Yellow
J	B-	REF SIN (SIN-)	REF COS	Nero – Black (Grigio – Grey)

Technical data and drawings are subject to change without notice.